






Identification

Product identifier : Acetone		Recommended use : Organic solvent used in industrial processes.	
Supplier(s) and last revision date(s) :		PRODUITS LUBRI-DELTA INC. 2014-11-03	Preventis Number : 0011734
  <p>Flammable liquids (Category 2). Eye irritation (Category 2). Specific target organ toxicity, single exposure, Narcotic effects (Category 3).</p>		<p>H225: Highly flammable liquid and vapour H319: Causes serious eye irritation H336: May cause drowsiness or dizziness</p>	
		   <p>Goggles Neoprene gloves (thin) Lab coat</p>	

Hazard identification



FLAMMABLE LIQUID! Keep away from heat, sparks and open flame. Avoid contact with skin, eyes and clothing. Do not breathe vapours, mists or aerosols. Do not ingest. If ingested consult physician immediately and show this Safety Data Sheet. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.

First-aid measures



Skin contact	Flush with water for at least 15 minutes. Remove contaminated clothing and wash before reuse. Avoid touching eyes with contaminated body parts. If a problem develops or persists, seek medical attention.
Eye contact	IMMEDIATELY flush with plenty of water. Remove contact lenses if easy to do. Flush with water for at least 15 minutes. Hold eyelids apart to rinse properly. If a problem develops or persists, seek medical attention.
Inhalation	Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen by trained personnel. If a problem develops or persists, seek medical attention.
Ingestion	DO NOT induce vomiting, unless recommended by medical personnel. If victim is conscious wash out mouth with water and give 1-2 glasses of water to drink. Never give anything by mouth if victim is unconscious or convulsing. If spontaneous vomiting occurs, keep head below hip level to prevent aspiration into the lungs. Seek medical attention or contact a Poison Centre immediately.
Other	No information available.

Always look after your own safety before helping a victim.

Health information



Eye contact	Eye Irritation, Rabbit (Male and Female): Test de Draize - highly irritating. Causes serious eye irritation.
Skin contact	Skin Irritation/Corrosion, Rabbit, (Male and Female) : Draize method is negative, no irritating. Prolonged and repeated contact may cause skin drying, cracking or irritation. redness, defatting dermatitis.
Inhalation	May cause slight upper respiratory tract irritation. Concentration threshold of irritation in humans: between 250 and 1000 ppm. High concentrations may cause central nervous system depression characterized by headache, dizziness, nausea, drowsiness, fatigue, unconsciousness. The severity of symptoms may vary depending on exposure conditions.
Ingestion	May cause gastrointestinal irritation with nausea and vomiting. Swallowing a large amount of this product may cause kidney damage, liver damage.
Respiratory or skin sensitization	Skin sensitisation, Buehler test, Mousse : not sensitizing. This product is not a skin or respiratory sensitizer.
Carcinogenicity	Not listed as a carcinogen by IARC, ACGIH, NIOSH, NTP or OSHA.
Mutagenicity	This material is not known to cause mutagenic effect.
Reproductive toxicity	This material is not known to cause effects on reproduction.
Specific target organ toxicity - single exposure	Central nervous system.
Specific target organ toxicity - repeated exposure	Blood.

Handling and storage



Keep away from heat, sparks and open flame. Avoid all sources of ignition. Avoid static electricity build up. Use non-sparking and antistatic tools. Ground/bond all containers when transferring large quantities (5 gallons US or 20 L and more). Use only in well ventilated area. Do not breathe vapours, mists or aerosols. Avoid contact with skin, eyes and clothing. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved. Keep only the quantities necessary for the work being performed in the work area. Keep containers tightly closed when not in use. Do not eat, do not drink and do not smoke during use. Wash hands, forearms and face thoroughly after handling this compound and before eating, drinking or using toiletries. Remove contaminated clothing and wash before reuse. Storage and handling should follow the NFPA 30 Flammable and/or Combustible Liquids Code and the National Fire Code of Canada (NFCC). Ground or bond large containers. Store tightly closed and in properly labelled containers in a cool, dry and well ventilated place. Containers that have been opened must be carefully resealed

and kept upright to prevent leakage. Store away from oxidizing materials and incompatible materials (see section 10). Store at a temperature between 10 and 20°C (50 et 68°F) Stable under recommended storage conditions. A dangerous reaction will not occur. Avoid heat, flame and sparks. Avoid contact with incompatible materials. **Incompatible materials** : Strong oxidants, strong bases, strong acids, bleach, activated carbon.

Minor Accidental Release Measures



Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet. No action shall be taken involving any personal risk or without suitable training. Evacuate unauthorized personnel. Remove sources of ignition. Ventilate the area well. Stop leak, if it's possible to do so without risk. Make sure you have a fire extinguisher near you. If necessary, reduce the concentration of vapor in air with water spray, taking care not to spread the product with run-off water. Absorb with inert material (soil, sand, vermiculite) or wipe up or scrape up and place in an appropriate waste disposal container clearly identified. Use non-sparking and antistatic tools. Dispose via a licensed waste disposal contractor. Finish cleaning by rinsing with water contaminated surface. Prevent entry in sewer and other enclosed area. For a large spill, consult the Department of Environment or the relevant authorities.

Fire-fighting measures



Powder carbon dioxide (CO₂), alcohol resistant foam, Do not use a heavy water jet.

To the best of our knowledge, the information contained herein is accurate. However, neither Prizventis System nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.